SIZES AND SPECIFICATIONS											
	SQUARE TAPERED			SQUARE NON-TAPERED				SQUARE NON-TAPERED PEDESTAL BASES			
NOMINAL COLUMN / Pedestal Sizes	10"	12"	16"	6"	8"	10"	12"	10" Colı	12" umn size sl	14" hould be 2"	16" less
36"								√ +	√ +	√ +	√ +
44"								√ +	√ +	√ +	√ +
5'	/ +	√ +	√ +								
6'	/ +	√ +	√ +	å +	/• +	/• +	/• +				
8'	/ +	√ +	√ +	å +	å +	å +	å +				
10'	/ +	√ +	√ +		/• +	å +	/• +				
12'						å +	å +				
Actual - Outside Shaft Width (bottom)	95/8	115/8	155/8	5 ⁵ / ₈	75/8	95/8	115/8	95/8	115/8	135/8	155/8
Actual - Outside Shaft Width (Top)	55/8	$7^{5}/_{8}$	$11^{5}/_{8}$	5 ⁵ / ₈	75/8	95/8	$11^{5}/_{8}$	95/8	$11^{5}/_{8}$	135/8	155/8
Actual - Inside Opening	43/8	63/8	103/8	43/8	63/8	83/8	10³/8	83/8	103/8	123/8	143/8
Pedestal Trim Width - PVC								115/8	135/8	155/8	175/8
Column Cap Width - PVC	95/8	115/8	155/8	7	9	11	13				
Column Base Width - PVC	135/8	155/8	195/8	7	9	11	13				

✓=Available Plain

• = Available Fluted

+ =Raised Panel

Optional:

Trimming to length, recess and panel positioning.

Installation Notes:

Columns are manufactured from Premium Cellular PVC and are not primed or painted. Non-Tapered caps and bases are assembled around column shaft. Tapered caps and bases attached to ends of column shafts. Panel and Recess columns can be trimmed a maximum of 6" for most sizes. Custom sizing available. Columns are decorative and are not load bearing. Trim, drill and fasten with traditional carpentry tools. Prime and paint with Acrylic Exterior Latex paint. Ten (10) Year limited warranty if installed according to installation instructions. Dimensions subject to change without notice.



E-Z Joint Column **Shaft Assembly**