

# SIZES AND SPECIFICATIONS

		ROUND TAPERED								ROUND NON-TAPERED								SQUARE TAPERED				SQUARE NON-TAPERED					
NOMINAL COLUMN SIZES		6"	8"	10"	12"	14"	16"	18"	20"	24"	8"	10"	12"	14"	16"	18"	20"	24"	9"	10"	12"	16"	6"	8"	10"	12"	14"
Total Height (Including caps & bases)	5'																		✓■	✓■	✓■						
	6'		✓	✓	✓		✓		✓										✓■	✓■							
	8'	✓	✓•	✓•	✓•	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				✓■			✓	✓•■	✓•■	✓■	✓
	9'		✓•	✓•	✓•	✓	✓	✓						✓	✓	✓	✓	✓					✓	✓•■	✓•■	✓•■	✓
	10'		✓•	✓•	✓•	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓						✓•■	✓•■	✓•■	✓
	12'			✓•	✓•	✓•	✓	✓	✓	✓		✓	✓	✓											✓	✓•	✓
	14'				✓	✓	✓	✓	✓	✓			✓	✓													✓
	16'				✓	✓	✓	✓	✓	✓			✓	✓													✓
	18'					✓	✓	✓	✓	✓																	
	20'					✓	✓	✓	✓	✓																	
	22'								✓	✓																	
	24'								✓	✓	✓																
Top Shaft - Outside Dia./Width		5 <sup>1</sup> / <sub>8</sub>	6 <sup>1</sup> / <sub>8</sub>	8	9 <sup>3</sup> / <sub>8</sub>	12	13 <sup>3</sup> / <sub>8</sub>	15 <sup>3</sup> / <sub>8</sub>	16 <sup>3</sup> / <sub>8</sub>	19 <sup>3</sup> / <sub>8</sub>	7 <sup>3</sup> / <sub>8</sub>	9 <sup>5</sup> / <sub>8</sub>	11 <sup>3</sup> / <sub>4</sub>	13 <sup>3</sup> / <sub>4</sub>	15 <sup>3</sup> / <sub>4</sub>	17 <sup>7</sup> / <sub>8</sub>	19 <sup>1</sup> / <sub>8</sub>	23 <sup>3</sup> / <sub>8</sub>	5 <sup>1</sup> / <sub>4</sub>	5 <sup>3</sup> / <sub>4</sub>	8 <sup>1</sup> / <sub>2</sub>	9	5 <sup>3</sup> / <sub>4</sub>	7 <sup>7</sup> / <sub>8</sub>	9 <sup>3</sup> / <sub>4</sub>	11 <sup>3</sup> / <sub>4</sub>	13 <sup>7</sup> / <sub>8</sub>
Bottom Shaft - Outside Dia./Width		5 <sup>3</sup> / <sub>4</sub>	7 <sup>5</sup> / <sub>8</sub>	9 <sup>5</sup> / <sub>8</sub>	11 <sup>7</sup> / <sub>8</sub>	13 <sup>7</sup> / <sub>8</sub>	15 <sup>3</sup> / <sub>4</sub>	17 <sup>1</sup> / <sub>4</sub>	19 <sup>3</sup> / <sub>4</sub>	23 <sup>3</sup> / <sub>4</sub>	7 <sup>5</sup> / <sub>8</sub>	9 <sup>5</sup> / <sub>8</sub>	11 <sup>3</sup> / <sub>4</sub>	13 <sup>3</sup> / <sub>4</sub>	15 <sup>3</sup> / <sub>4</sub>	17 <sup>7</sup> / <sub>8</sub>	19 <sup>1</sup> / <sub>8</sub>	23 <sup>3</sup> / <sub>8</sub>	8 <sup>1</sup> / <sub>2</sub>	9 <sup>1</sup> / <sub>4</sub>	11 <sup>1</sup> / <sub>4</sub>	16	5 <sup>3</sup> / <sub>4</sub>	7 <sup>7</sup> / <sub>8</sub>	9 <sup>3</sup> / <sub>4</sub>	11 <sup>3</sup> / <sub>4</sub>	13 <sup>7</sup> / <sub>8</sub>
Tuscan Cap Width - Foam		8	9 <sup>3</sup> / <sub>4</sub>	12 <sup>1</sup> / <sub>4</sub>	14 <sup>1</sup> / <sub>4</sub>	16 <sup>5</sup> / <sub>8</sub>	19 <sup>1</sup> / <sub>8</sub>	21 <sup>3</sup> / <sub>8</sub>	24 <sup>3</sup> / <sub>8</sub>	27 <sup>4</sup> / <sub>8</sub>	9 <sup>3</sup> / <sub>4</sub>	12 <sup>1</sup> / <sub>4</sub>	14 <sup>3</sup> / <sub>4</sub>	16 <sup>3</sup> / <sub>8</sub>	21 <sup>1</sup> / <sub>4</sub>	24 <sup>1</sup> / <sub>4</sub>	28 <sup>3</sup> / <sub>4</sub>	32 <sup>1</sup> / <sub>2</sub>	8 <sup>3</sup> / <sub>8</sub>	8 <sup>3</sup> / <sub>8</sub>	13 <sup>7</sup> / <sub>16</sub>		8 <sup>3</sup> / <sub>8</sub>	11 <sup>1</sup> / <sub>4</sub>	13 <sup>3</sup> / <sub>4</sub>	16 <sup>1</sup> / <sub>8</sub>	18 <sup>1</sup> / <sub>4</sub>
Tuscan Base Width - FRP		8 <sup>1</sup> / <sub>8</sub>	10 <sup>1</sup> / <sub>8</sub>	13 <sup>1</sup> / <sub>8</sub>	15 <sup>1</sup> / <sub>2</sub>	18 <sup>3</sup> / <sub>8</sub>	21 <sup>1</sup> / <sub>4</sub>	24	26 <sup>1</sup> / <sub>2</sub>	32	10 <sup>1</sup> / <sub>8</sub>	13 <sup>1</sup> / <sub>8</sub>	15 <sup>1</sup> / <sub>2</sub>	18 <sup>3</sup> / <sub>8</sub>	21 <sup>1</sup> / <sub>4</sub>	24	26 <sup>1</sup> / <sub>2</sub>	32	13 <sup>7</sup> / <sub>16</sub>	13 <sup>7</sup> / <sub>16</sub>			8 <sup>3</sup> / <sub>8</sub>	10 <sup>1</sup> / <sub>2</sub>	13	14 <sup>7</sup> / <sub>8</sub>	17 <sup>5</sup> / <sub>8</sub>
Load Bearing (Roof Loads)		6M 10M 14M 18M								6M 10M 14M												6M 10M 14M 18M					

✓ = Available Plain      • = Available Fluted      ■ = Recessed Panel      M = Thousand

**Optional:** Trimming to length, splitting in half to wrap around existing post. Tuscan aluminum bases (see Optional Caps & Bases page). Ornamental capitals (see Optional Caps & Bases page).

**Installation Notes:** Columns are not primed or painted. Caps and bases are hollow and slide around column shaft. Fluted, Panel and Recess columns can be trimmed a maximum of 5" for most sizes.

Dimensions are subject to change without notice. Ten (10) year limited warranty if installed according to installation instructions.

Load capacities are for roof loads only and are reduced if loads are not centered. Balconies, floors and 8' uplift applications require an internal structural support inside. Pergolas, trellises and other free standing applications require an internal structural support inside. Columns not covered by a roof require flashing at the top of column to prevent water and snow collection. Concrete support footings must be below grade. Do not pour concrete or sand inside column shaft.